

# (12) United States Patent

## Caskey et al.

## (54) MULTI-PANEL ELECTRONIC DEVICE

Inventors: Mark S. Caskey, San Diego, CA (US); Sten Jorgen Ludvig Dahl, San Diego, CA (US); Sherman A. Gregory, San

Diego, CA (US)

Assignee: QUALCOMM Incorporated, San

Diego, CA (US)

Subject to any disclaimer, the term of this Notice:

patent is extended or adjusted under 35

U.S.C. 154(b) by 1116 days.

Appl. No.: 12/553,829

(22)Filed: Sep. 3, 2009

**Prior Publication Data** (65)

> US 2010/0064536 A1 Mar. 18, 2010

## Related U.S. Application Data

- Provisional application No. 61/095,225, filed on Sep. 8, 2008, provisional application No. 61/182,316, filed on May 29, 2009.
- (51) Int. Cl. G01C 17/00 (2006.01)(2006.01)G06F 1/16 (Continued)
- (52) U.S. Cl.

CPC ...... G06F 1/1694 (2013.01); G01C 17/00 (2013.01); G06F 1/1616 (2013.01); G06F 1/1641 (2013.01); G06F 1/1649 (2013.01); G06F 1/1654 (2013.01); G06F 1/1677 (2013.01); G06F 1/1684 (2013.01); G06F 3/1446 (2013.01); G06F 2200/1614 (2013.01); G06F 2200/1635 (2013.01); G06F 2200/1637 (2013.01); G09G 5/14 (2013.01); (Continued)

## (10) Patent No.:

US 9,009,984 B2

(45) Date of Patent:

Apr. 21, 2015

## Field of Classification Search

CPC ....... G01C 17/00; G01C 17/04; G01C 17/30; G01C 17/28; G01C 17/18; G01C 17/38; G01C 17/26; G01R 33/025 See application file for complete search history.

#### (56)References Cited

### U.S. PATENT DOCUMENTS

6,133,898 A 10/2000 Ludolph et al. 6/2001 Tada et al. 6,252,563 B1 (Continued)

## FOREIGN PATENT DOCUMENTS

1484068 A CN3/2004 CN1575117 A 2/2005 (Continued) OTHER PUBLICATIONS

International Search Report & Written Opinion—PCT/US2009/ 056286, International Search Authority—European Patent Office— Dec. 17, 2009.

(Continued)

Primary Examiner — Yaritza Guadalupe-McCall (74) Attorney, Agent, or Firm — James R. Gambale, Jr.

## ABSTRACT

A multi-panel electronic device and method are disclosed. In a particular embodiment, a method includes receiving first acceleration data from a first sensor coupled to a first portion of an electronic device. The method further includes receiving second acceleration data from a second sensor coupled to a second portion of the electronic device, where a position of the first portion is movable with respect to a position of the second portion. The method further includes determining a configuration of the electronic device at least partially based on the first acceleration data and the second acceleration data.

## 37 Claims, 36 Drawing Sheets

